

PALM

D23-32

(120V)

FOC

Freedom Of Creation
Cruquiuskade 85-87
1018 AM Amsterdam
The Netherlands

Tel/Fax +31 (0) 20 675 84 15

www.freedomofcreation.com
info@freedomofcreation.com



Instructions

1. Connect the mounting unit (2) to the ceiling with the included attachment screws (1). If you need to drill a hole in the ceiling, use 8mm diameter drill bit.
2. Connect one of the tension releases (3) to the cone (4).
3. Pull the cable (5) through the lampshade and fix them together with the other tension release (3).
4. Pull the other end of the cable through the cone (4) and cut your cable according to your length wishes.
5. Tighten the screws on both of the tension releases (3), so that the cable (5) is fixed.
6. Use the terminal block (6) to connect the cables to the electric output in your ceiling. The cables are not polarized, so you can connect them either way.
7. Place the cone (4) on the mounting unit (2) and turn so that the cone locks in place.
6. Push the bulb (7) in the fitting and enjoy your new light.

Which bulb to use?

- Osram 110-130 V, 15-40 W, G9 (Japan, USA) **ONLY USE OSRAM BULBS!!!**

How to clean the shade?

- You can clean your product easily with standard soap.

How is this product made?

This product is made in layers by a Laser Sintering machine. In fact your product originated as a 3-dimensional computer file. Due to the manufacturing method none of the products are identical, resulting in a unique item with its own characteristics.

ATTENTION!!!

- **FOR INDOOR USE ONLY!**
- **DO NOT CHANGE THE BULB WHILE THE LIGHT IS ON**
- **USE MAXIMUM 40 WATT OSRAM G9 BULBS!**
- **DO NOT COVER THE LAMP!**
- **YOUR PRODUCT IS NOT A HEAVY DUTY ITEM, BUT IS A WORK OF ART. PLEASE TREAT IT CAREFULLY!**
- **DUE TO THE CHEMICAL PROPERTIES OF POLYAMIDE 22, THE SHADE OF YOUR LIGHTING FIXTURE WILL BECOME A STABLE OFF WHITE COLOR AFTER 4000 HOURS OF USAGE**